



type	Dia	lead	Ball	Turn	Curcuit	Main Dimension										Load	
						D1 (g6)	D2-0.0015	D3	D4	D5	L1	L2	B	G	H1	Ca	Coa
SFU1204-3	12	4	2.381	3	22/24	21.5	42	32	4.8	35	10	8	M6	30	592	1129	
SFU1605-3	16	5	3.175	3	28	27.8	48	38	5.5	42	10	10	M6	40	780	1790	
SFS1610-3	15	10	2.778	3	28	27.8	48	38	5.5	57	10	10	M6	40	736	1275	
SFU2005-3	20	5	3.175	3	36	35.8	58	47	6.7	42	10	10	M6	44	860	1710	
SFS2010-3	20	10	3.175	3	36	35.8	58	47	6.7	67	10	10	M5	40	996	2296	
SFU2505-3	25	5	3.175	3	40	39.8	63	51	6.7	42	10	10	M6	48	980	2300	
SFU2505-4	25	5	3.175	4	40	39.5	63	51	6.7	51	10	10	M6	48	1280	3110	
SFU2510-3	25	10	4.763	3	40	39.5	62	51	6.8	85	16	15	M6	48	870	2050	
SFU3205-3	32	5	3.175	3	50	49.8	80	65	9	55	10	12	M6	62	1690	5100	
SFU3205-4	32	5	3.175	4	50	49.8	80	65	9	52	10	12	M6	62	1450	4150	
SFU3210-3	32	10	6.35	3	50	49.5	80	65	9	74	16	12	M6	62	2610	5310	
SFU3210-4	32	10	6.35	4	50	49.5	80	65	9	90	16	14	M6	62	3390	7170	
SFU4005-4	40	5	3.175	4	63	62.5	93	78	9	55	16	15	M6	70	1610	5330	
SFU4005-5	40	5	3.175	5	63	62.5	93	78	9	55	10	14	M6	70	1900	6620	
SFU4010-3	40	10	6.35	3	63	62.5	93	78	9	71	16	14	M6 M8	70	3010	7100	
SFU4010-4	40	10	6.35	4	63	62.5	93	78	9	93	16	15	M6 M8	70	3910	9520	
SFU5005-4	50	5	3.175	4	75	74.5	110	93	11	55	16	15	M6 M8	85	1880	6690	
SFU5010-4	50	10	6.35	4	75	74.5	110	93	11	95	16	16	M6 M8	85	5310	15500	
SFU6310-4	63	10	6.35	4	90	/	125	108	11	97	/	18	M8	95	5070	16600	
SFU6310-5	63	10	6.35	5	90	/	125	108	11	97	/	18	M8	95	6070	20600	
SFU8010-5	80	10	6.35	5	105	/	145	125	13.5	108	/	20	M8	110	6660	26500	
SFU8010-6	80	10	6.35	6	105	/	145	125	13.5	110	/	22	M8	110	7810	31800	

Ca Coa: kgf 1kgf=9.8N