





This kit comes with everything you see here. Plus 8 each: 5mm x 20mm stainless steel cap screws. 4 each: 4mm x 16mm stainless steel cap screws for Z motor. 4 each: 4mm x 12mm stainless steel cap screws for X motor. 2 each: 2 shim washers, just in case. 2 plastic tubes for the ball nuts. These are added just in case you need to remove one of the ball nuts from the ball screw. Go to Thomson Linear web site for video instructions on how to safely remove the ball nut from the ball screw.





Start by removing all of the handles

---



Remove the plates from both ends of the table

---



Remove the piece circled in red

---




Now the table will slide off of the saddle


Loosen the two set screws and the lead screw nut will come off with the lead screw

---





Move the head to the top of the column. Loosen the bolts for the head and rotate it 90 degrees. This will expose the bolts for the lead screw nut in Z. You can also just remove the head. It will make things easier, later




Take off everything on top of the column

---



Also remove everything from Z handle

---



Remove the bolts from behind the head. Screw the lead screw until the lead nut gets to the slot in the column. Take the block off as shown, then you can pull the lead screw out from the top



At this point you'll need to take the column off of the base. It's not a bad idea to remove the head first. It makes managing this easier





Unscrew the lead screw from the nut, and remove the nut, and lead screw

---



You will need to remove some material to get the new ball screw to go in the base

---





We used a manual mill to do this...because we have one. You may have to use a grinder. You'll be removing however much it takes to get the ball screw in. I wish I could be more precise, but casting are different.





The finish machining


You'll need to machine the saddle as well. To fit the ball nuts for X













Now you can start the installation. You will need to remove the washer and snap ring.

---



Remove the .25" plate from the Y assembly, and bolt the rest of the assembly to the base


---




Tighten down the new ball nut block where the old one was




Put the column and the milling head back onto the base



- Drop the Z ball nut block down into the column as shown. When it gets to the through slot, you can tilt it to get it through the slot to align with the bolt holes





Drop the ball screw with the flange on it down through the ball nut block, and bolt the flange to the block.